



NestaFlex

Gravity 376 AL/FL Skate Wheel Conveyor

* Specifications of models available may vary from the model shown

FEATURES

WIDTH: 18", 24", or 30"

Determined by package size, available conveying area and application specific needs

LENGTH EXTENDED: 8' - 60'

Determine total length needed, including curvatures and obstructions

AXLE CENTER: 5.25", 4" or 3"

Package size determines necessary axion center length on fully extended conveyor

SKATE WHEEL TYPE: STEEL, BLACK, RED

Determined by package weight, durabil ity, operational flow control, and application specific needs

DESCRIPTION

The NestaFlex® 376 AL/FL is a heavy duty, gravity conveyor that features double welded cross braces and heavy duty square tubing legs available in adjustable height legs (AL) and fixed height legs (FL). This all bolted design uses shoulder bolts, steel lock nuts and is additionally secured with industrial thread lock to help reduce maintenance. The four point leg connection gives additional strength to the conveyor to make it last longer. The NestaFlex 376 is designed to provide the support necessary to handle heavy packages in high volume environments.

The NestaFlex® 376 AL/FL has a proven track record in the industry and is the choice for medium to high volume shipping and receiving departments in distribution centers, retail stores, and manufacturing and assembly operations.








NestaFlex

SPECIFICATIONS

Gravity 376 AL/FL Skate Wheel Conveyor





| 18" Wide Models | | 24" Wide Models | | 30" Wide Models | | Length Adjustments | |
|-----------------|----------|-----------------|----------|-----------------|----------|--------------------|------------|
| Model # | Leg Sets | Model # | Leg Sets | Model # | Leg Sets | Extended | Contracted |
| 37618008 | 3 | 37624008 | 3 | 37630008 | 3 | 8′ 6″ | 2′ 7″ |
| 37618012 | 4 | 37624012 | 4 | 37630012 | 4 | 12′ 2″ | 3′ 7″ |
| 37618016 | 5 | 37624016 | 5 | 37630016 | 5 | 15′ 10″ | 4′ 8″ |
| 37618020 | 6 | 37624020 | 6 | 37630020 | 6 | 19′ 6″ | 5′ 8″ |
| 37618024 | 7 | 37624024 | 7 | 37630024 | 7 | 23′ 2″ | 6′ 8″ |
| 37618028 | 8 | 37624028 | 8 | 37630028 | 8 | 28′ 0″ | 8′ 2″ |
| 37618032 | 9 | 37624032 | 9 | 37630032 | 9 | 31′ 8″ | 9′ 2″ |
| 37618036 | 10 | 37624036 | 10 | 37630036 | 10 | 35′ 4″ | 10′ 3″ |
| 37618040 | 12 | 37624040 | 12 | 37630040 | 12 | 41′ 10″ | 12′ 1″ |
| 37618044 | 13 | 37624044 | 13 | 37630044 | 13 | 45′ 6″ | 13′ 1″ |
| 37618048 | 14 | 37624048 | 14 | 37630048 | 14 | 49′ 5″ | 14′ 4″ |
| 37618052 | 15 | 37624052 | 15 | 37630052 | 15 | 53′ 1″ | 15′ 4″ |
| 37618056 | 16 | 37624056 | 16 | 37630056 | 16 | 56′ 9″ | 16′ 5″ |
| 37618060 | 17 | 37624060 | 17 | 37630060 | 17 | 60′ 5″ | 17′ 5″ |

All conveyor products can be modified to suit specific design requirements. Please contact our sales representatives for details on sizes or options that are not listed

STANDARD FEATURES

Load capacity 376 lbs/ft

Steel skate wheels with steel ball bearings

5.25" axle centers

28" – 36" adjustable conveyor heights (AL ONLY) using hand knobs to raise or lower the legs for 5" casters; 29" – 37" for 6" casters

Fixed leg (FL ONLY) height adjustments determined per application and are preset by set screws or hand knob

Heavy duty steel square tubing zinc plated legs

Welded double horizontal leg braces

Heavy duty 5" x 1 ½" casters with 2 total lock brake casters on each end (all conveyors up to 40' in length); 6" x 2" (all conveyors over 40' in length)

5/16" diameter axle across the width

Self-tracking design

Couplers easily connect two or more conveyors Heavy duty retractable package stop

OPTIONS

4" and 3" axle centers

Additional brake casters

Additional set of couplers

Additional leg height adjustments (AL ONLY):

5" casters: 20"-26"; 24"-32"; 26"-44"; 44"-52"

6" casters: 21"-27"; 25"-33"; 37"-45"; 45"-53"

Black poly skate wheels with steel ball bearings and red poly skate wheels with nylon bushings

Caster upgrades - 6" or 8"

Outboard couplers

36" conveyor width

ACCESSORIES

Curve Guards Side Handles

Swing Stick Heavy Duty Impact Cart

T-Junction

Technical Data

CONSTRUCTION

All steel bolted construction

LEGS

Zinc plated, heavy duty leg supports 1 1/4", square steel tubing with a double welded cross brace

SIDE LINKS

Made of 7 gauge steel assembled using shoulder bolts with Loctite and steel locking nuts

WARRANTY

24 month factory warrants

SERVICES AVAILABLE

Technical Support
Installation and Setup
Maintenance
Application Support

Hardware Support

FMH Conveyors LLC 410 Horizon Drive Suwanee, GA 30024 www.fmhconveyors.com 1.800.669.1501



THE **DURAVANT** FAMILY OF COMPANIES

MARLEN INTERNATIONAL | FISCHBEIN | HAMER | MESPACK | FMH CONVEYORS