

FEATURES

WIDTH: 14", 18" or 24"

Determined by package size, available conveying area and application specific needs

LENGTH EXTENDED: 8' - 60'

Determined by total length needed, including curvatures and obstructions

AXLE CENTER: 51/4", 4" or 3"

Package size determines necessary axle center length on fully extended conveyor

SKATE WHEEL TYPE: STEEL, BLACK, RED

Determined by package weight, durability, operational flow control, and application specific needs



DESCRIPTION

Designed to expand, contract and move easily, the **NestaFlex**® **226** is a self tracking, gravity skate wheel conveyor that has a per linear foot capacity of 226 pounds. This unit is engineered to handle multi-sized cartons in low to medium volume applications.

The all-steel construction provides unmatched structural integrity, whether the conveyor is extended, compacted or configured in simple or compound curves. Adjustable inner legs vary height to achieve gravity flow.

The **NestaFlex 226** is the choice for use in retail store level applications, packaging areas, assembly lines and in low volume shipping and receiving departments.





GRAVITY 226 SKATE WHEEL CONVEYOR





SPECIFICATIONS

14" WIDTHS							
Model #	Leg Sets						
22614008	3						
22614012	4						
22614016	5						
22614020	6						
22614024	7						
22614028	8						
22614032	9						
22614036	10						
22614040	11						

6 ѕкате	wneels	per ax	ıe

18" WIDTHS		ı	24" WIDTHS		ı	LENGTH ADJUSTMENT		
Model #	Leg Sets	ı	Model #	Leg Sets	ı	Extended	Contracted	
22618008	3	ı	22624008	3	ı	8′ 11″	2′ 4″	
22618012	4	ı	22624012	4	ı	12′ 10″	3′ 3″	
22618016	5	ı	22624016	5	ı	16′ 9″	4′ 3″	
22618020	6	ı	22624020	6	ı	20′ 9″	5′ 2″	
22618024	7	ı	22624024	7	ı	24′ 8″	6′ 2″	
22618028	8	ı	22624028	8	ı	28′ 7″	7′ 1″	
22618032	9	ı	22624032	9	ı	32′ 6″	8′ 1″	
22618036	10	ı	22624036	10	ı	36′ 6″	9′ 0″	
22618040	11	ı	22624040	11	ı	40′ 5″	10′ 0″	
22618044	12	ı	22624044	12	ı	44′ 4″	10′ 11″	
22618048	13	ı	22624048	13	ı	48′ 3″	11′ 11″	
22618052	14		22624052	14	ı	52′ 3″	12′ 10″	
22618056	15		22624056	15	ı	56′ 2″	13′ 10″	
22618060	16		22624060	16	ı	60′ 1″	14′ 9″	

8 skate wheels per axle

8 skate wheels per axle

With standard 51/4" axle center

All conveyor products can be modified to suit specific design requirements.

Please contact our sales representatives for details on sizes or options that are not listed.

STANDARD FEATURES

Load capacity 226 lbs/ft

Black poly skate wheels with steel ball bearings

51/4" axle centers

28" – 44" adjustable conveyor heights using hand knobs to raise or lower the legs

Heavy duty steel square tubing zinc plated legs

Welded horizontal leg brace

Heavy duty 5" x 1½" casters with 2 total lock brake casters on each end

11 gauge steel side links assembled using steel pin and retaining ring

5/16" Ø axle across the width

Self-tracking design

Couplers

Heavy duty retractable package stop

OPTIONS

4" and 3" axle centers Additional brake casters Additional set of couplers

Elevations for Adjustable legs

20"-28"

25"-38"

36"-52"

Steel skate wheels / steel ball bearings OR Red poly skate wheels / nylon bushings

ACCESSORIES

Curve Guards Swing Stick T-Junction

TECHNICAL DATA

CONSTRUCTION

All steel construction

LEGS

Zinc plated, heavy duty leg supports 11/8" square steel tubing with a welded cross member

SIDE LINKS

Made of 11 gauge steel

WARRANTY

18 month warranty

SERVICES AVAILABLE

Technical Support
Application Support
Hardware Support

FMH Conveyors 9701 E. Highland Drive Jonesboro, AR 72401



FMHConveyors.com 1.800.327.9209



THE **DURAVANT** FAMILY OF COMPANIES

MARLEN INTERNATIONAL | FISCHBEIN | HAMER | MESPACK | FMH CONVEYORS

www.duravant.com